

BCD-HES02-I5-I7-8RJ

2-Bay Small Form Factor Harsh Environment Server

8 PORT POE HARSH ENVIRONMENT SERVER

This BCD-HES02-I5/I7-8RJ support 8-port Gigabit PoE and able to work under harsh temperatures.

Its eight Gigabit PoE ports allow multiple cabling to cameras and any PoE power device. Powered by an Intel® Core™ i5 or i7 processor, this unit also has SIM slots and SMA-type antenna connectors.

For storage, this high performance fanless server has two drive bays with a height of up to 15 mm and one M.2 SSD for RAID 0 and 1. Moreover, the embedded device supports two 260-pin DDR4 SO-DIMM slots for up to 64GB of system memory.



KEY FEATURES

- ▶ Up to 8TB Storage
- ▶ Intel® Core™ 10th Generation Processors
- ▶ Up to 64GB DDR4 RAM, optional with ECC
- ▶ Windows 10 Pro/Linux
- ▶ Supports Cell, GPS, and WiFi modules
- ▶ -40°C to +75°C (-40°F to +167°F) with Wide Temp SSDs
- ▶ (8) RJ45 PoE Ports
- ▶ 2-year Standard Warranty

FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993

TECH SUPPORT: support@bcdinc.com

Copyright © 2026, BCD. All rights reserved. This document is provided for information purposes only. Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

BCD-HES02-I5-I7-8RJ

2-Bay Small Form Factor Harsh Environment Server

SYSTEM

Certifications

CE
FCC Class A
IP40

Expansion Slots

(1)PCIe Mini Card Slot, (1) M.2 Key B
(1) M.2 Key E, (2)Mini PCIe

I/O Ports

(3) External Nano SIM Sockets for 5G/ WiFi
6/4G/3G/LTE/GPRS/UMTS
6-port USB 3.2 support up to 10Gbps data transfer
32 Isolated DIO, 4 COM RS-232/422/485 Serial: 4 COM
RS-232/422/485 (ESD 8KV)

Memory

Standard Configuration: 16GB (2x 8GB)
Maximum Configuration: Up to 64 GB , optional with
ECC (2x DDR4 SO-DIMM Slots)

Networking

(8)1GbE RJ45 PoE Ports (IEEE 802.3af/802.3at)
(2)1GbE Non-PoE RJ45 Ports

Operating System

Windows 10 Pro /Linux

Processor Passmark

Intel® Core™ i5-10500TE: 9,960
Intel® Core™ i7-10700TE: 16,332

Processor(s)

(1)Intel® Core™ 10 th Generation i5 Processor (Up to 6
Cores, 12 Threads, 3.7 GHz)
(1)Intel® Core™ 10th Generation i7 Processor (Up to 8
Cores, 16 Threads, 4.4GHz)

Video Outputs

(1)VGA
(1) DVI-D
(2) DisplayPort interfaces, up to 4K resolution

MECHANICAL

Dimensions (WxDxH)

10.24 " x 9.45 " x 3.11 " (260mm x 240mm x
79mm)

EMC

CE
FCC
EN50155
EN50121-3-2

Form Factor

Small Form Factor

Manufacturer

BCD

Max. Weight

9.92 lb (4.5 kg)

Operating Humidity

95% at 75°C

Operating Temperature

35W TDP CPU : -40°C to 75°C (-40°F to 167°F),

Fanless

65W TDP CPU : -40°C to 55°C (-40°F to 131°F),

Fanless

80W & 95W TDP CPU : -40°C to 55°C (-40°F to

131° F), with Fan Sink

Power Supply(s)

Power Input: 9V to 50V, DC-in

Power Interface: 3-pin Terminal Block : V+, V-,

Frame Ground

Ignition Control: 16-mode Software Ignition Control

Remote Switch: 3-pin Terminal Block

Surge Protection: Up to 80V/1ms Transient Power

Shock Endurance

IEC 60068-2-27 (with SSD, 50G, half sine, 11ms
duration)

Vibration Endurance

IEC 60068-2-64 (with SSD, 5 Grms STD, random 5
to 500 Hz, 3 axis)

Warranty

2 -Year Standard

STORAGE

Hard Drive Bays

(1)256GB m.2
(2)15mm 2.5" Drive Bays

Hard Drives Supported

SATA

Maximum Storage

Up to 8TB

RAID

JBOD