

BCD228X-EVS

BCD Enterprise 2U 28-Bay Rackmount Video Recording Server

MAXIMUM STORAGE DENSITY VIDEO SERVER BUILT FOR ENTERPRISE PROJECTS

Benefit from next-generation video data archiving and processing with the enterprise BCD228X-EVS-416S 2U 28-Bay rackmount server. With up to 672TB of raw storage, this video server will be a long-term storage solution for the most demanding projects.

Powered by (2) of the latest Intel® Xeon® Gold Scalable Processors, the BCD228X-EVS-416S ensures performance. Memory bandwidth is readily available with (16) DIMM slots for up to 1TB of DDR5 DIMM memory, ensuring system resources are always available for high-intensity applications.

System reliability is at the forefront, with (2) 1400W redundant, hot swappable power supplies, as well as RAID 0/1/5/6/10 storage options to help preserve data integrity and provide maximum performance, while a five-year, on-site, next business day, Keep Your Hard Drive warranty ensures peace of mind.

All appliances are built in-house in BCD's secure facilities. BCD's operations have been assessed by DQS Inc, who certified that we meet the ISO 9001:2015 standard of maintaining a Quality Management System.

KEY FEATURES

- ▶ Up to 672TB Storage
- ▶ Intel® Latest Processor
- ▶ Windows Server
- ▶ SSD & SAS Drives
- ▶ RAID Options 0, 1, 5, 6, 10
- ▶ 5-Year On-site, NBD, Keep Your Hard Drive Warranty
- ▶ iDRAC Express



FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993

TECH SUPPORT: support@bcdinc.com

Copyright © 2026, BCD. All rights reserved. This document is provided for information purposes only. Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

BCD228X-EVS

BCD Enterprise 2U 28-Bay Rackmount Video Recording Server

SYSTEM

Expansion Slots

(3) PCIe x 16 low-profile slots

Memory

Standard Configuration: (4x GB) 64GB 16

Maximum Configuration: Up to 1TB RDIMM,

1TB LRDIMM (16x DDR DIMM Slots) 5

Networking

(2)1GbE RJ45 Ports

(2) 10 GbE SFP ports /2528

Operating System

Windows Server

Processor Passmark

Dual Intel® Xeon® : Gold 5416S 63,499

Processor(s)

(2) Intel® Xeon® Scalable Gold 5416S

Processors (16 Cores, 32 Threads, 3.20GHz)

Remote Management

iDRAC Express

USB(s)

Rear (1) USB .012 , (1) USB 3.0

Front (1) USB 3.0 (1) Micro USB 3.0 Internal

(1) USB 3.0

Video Outputs

(1)VGA

MECHANICAL

Dimensions (WxDxH)

18.96" (481.6mm) x 32.95" (837mm) x

3.41" (86.8mm)

Form Factor

2U Rackmount

Heat Dissipation

3001 Max BTU/hr

Manufacturer

BCD

Max. Weight

102.07 lbs. (46.3 kg)

Operating Humidity

10 ~ 80% (non-condensing)

Operating Temperature

(Min) 50°F - (Max) 86° F[(Min) 10°C -

(Max) 30° C]

Power Supply(s)

(2) 1400W (100-240VAC) 80 Plus

Platinum

Warranty

5-Year, On-site, Next Business Day, Keep

Your Hard Drive Warranty

STORAGE

Hard Drive Bays

(2)3.5" Hot Swappable Bays, 8

(2) M.2480GB OS Drives

Hard Drives Supported

PCIe NVMe

SAS

Maximum Storage

Up to 672TB of Raw Storage

RAID

RAID 0, 1, 56, 10

RAID Controller

PERC H 965i