

BCDT03-ELVS

BCD Entry-Level 3-Bay Tower Video Recording Server

STORAGE DENSE, HIGH PERFORMANCE ENTRY-LEVEL 3-BAY TOWER VIDEO SERVER

The professional BCDT03-ELVS enables maximum storage and throughput in a space-efficient tower. Up to (3) 3.5" 24/7 duty cycle SATA drives providing up to 72TB of raw storage, providing room for future scalability.

The BCDT03-ELVS comes equipped with the latest Intel® Core™ Ultra Processors. Support for up to 128GB of DDR5 memory allows for plentiful local resources, while a NVMe M.2 solid state drive accelerates boot and application load times for increased performance and a reliable user experience.



KEY FEATURES

- ▶ Up to 60TB Storage
- ▶ Intel® Latest Processor
- ▶ Windows 11 Pro
- ▶ SSD & 24/7 Duty Cycle SATA Drives
- ▶ 5-Year, On-site, NBD Warranty

FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993

TECH SUPPORT: support@bcdinc.com

Copyright © 2026, BCD. All rights reserved. This document is provided for information purposes only. Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

BCDT03-ELVS

BCD Entry-Level 3-Bay Tower Video Recording Server

SYSTEM

Expansion Slots

- (1) full-height Gen5 PCIe x16 slot
- (1) full-height, half-length Gen3 x4 PCIe closed-end slot
- (1) full-height, full-length Gen4 x4 PCIe open-end slot
- (1) full-height, full-length Gen3 x4 PCIe open-end slot

Memory

- 16GB DDR5 (2x 8GB)
- Maximum Configuration Supported 128GB (4x 32GB)

Networking

- (1) 1GbE RJ45 Ports

Operating System

- Windows 11 Pro

Processor Passmark

- Intel Core Ultra 5235: 40,026
- Intel Core Ultra 5245K: 43,451
- Intel Core Ultra 7265K: 58,805
- Intel Core Ultra 9285K: 67,641

Processor(s)

- Intel Core Ultra 5235: 14 cores, 14 threads, 2.9 GHz to 5.0 GHz
- Intel Core Ultra 5245K: 14 cores, 14 threads, 3.6 GHz to 5.2 GHz
- Intel Core Ultra 7265K: 20 cores, 20 threads, 3.3 GHz to 5.5 GHz
- Intel Core Ultra 9285K: 24 cores, 24 threads, 3.2 GHz to 5.7 GHz

USB(s)

- Front: (1) USB 3.2 Gen 1 (5 Gbps) port - (1) USB 3.2 Gen 1 (5 Gbps) port with PowerShare - (1) USB 3.2 Gen 2 (10 Gbps) Type-C port - (1) USB 3.2 Gen 2x2 (20 Gbps) Type-C port with PowerShare
- Rear: - (2) USB 2.0 (480 Mbps) ports with SmartPower - (2) USB 3.2 Gen 2 (10 Gbps) ports - (1) Thunderbolt4 port - (1) USB 3.2 Gen 2x2 (20 Gbps) Type-C port

Video Outputs

- (2) DisplayPort 1.4a (HBR3) port
- (1) VGA Port

MECHANICAL

Dimensions (WxDxH)

- Height: 387.00 mm (15.24 in.) Width: 187.70 mm (7.40 in.) Depth: 438.00 mm (17.24 in.)

Form Factor

- Tower

Heat Dissipation

- 5115 BTU/hr

Manufacturer

- BCD

Max. Weight

- 20.40 kg (44.97 lbs.)

Operating Humidity

- 10% to 90% (non-condensing)

Operating Temperature

- 0°C to 35°C (32°F to 95°F)

Power Supply(s)

- 1500W Platinum (90 VAC-264 VAC)

Warranty

- 5-Year, On-site, Next Business Day Warranty

STORAGE

Hard Drive Bays

- (2) M.22230/2280

Hard Drives Supported

- PCIe NVMe

- SATA

Maximum Storage

- Up to 72TB