

MON-24-FHD

24 Inch Client Viewing Monitor with Full HD

The 23.8" LED-backlit LCD Monitor features a VA panel for stunning Full HD (1080p) visuals at 60 Hz. Enjoy vibrant colors and sharp images with a high contrast ratio of 3000:1 and a wide color gamut of 72% NTSC (CIE 1931) and 83% NTSC (CIE 1976). With a 5ms gray-to-gray fast response time and adjustable positions, this monitor offers both performance and comfort for work or entertainment.



KEY FEATURES

- ▶ LED-backlit LCD Monitor / TFT Active Matrix
- ▶ 16:9
- ▶ Full HD (1080p) 1920 x 1080 at 60 Hz
- ▶ LED Backlight
- ▶ 5Year 24/7 ProSupport and Advanced Exchange Warranty

FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993

TECH SUPPORT: support@bcdinc.com

Copyright © 2026, BCD. All rights reserved. This document is provided for information purposes only. Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

MON-24-FHD

24 Inch Client Viewing Monitor with Full HD

GENERAL

Aspect Ratio

16:9

Backlight Technology

LED Backlight

Brightness

2250 cd/m

Color Gamut

72% NTSC (CIE 1931), 83% NTSC (CIE 1976)

Contrast Ratio

3000:1 / 3000:1 (dynamic)

Diagonal Size

23.8"

Display Type

LED-backlit LCD Monitor / TFT Active Matrix

Native Resolution

Full HD (1080p) 1920 x 1080 at 60 Hz

Panel Type

VA

Response Time

Response Time

AUDIO

Speakers

Stereo

CONNECTIVITY

Connectivity Interfaces

(1) DisplayPort 1.2

(1) VGA

(1) HDMI

MON-24-FHD

24 Inch Client Viewing Monitor with Full HD

ENVIRONMENTAL

Environmental Standards

EPEAT Compliant: EPEAT Gold

ENERGY STAR Certified: Yes

Humidity Range Operating

10 - 80% (non-condensing)

Operating Temperature

32 °F - 104°F (0°C - 40°C)

SUPPORT

Warranty

5Year 24/7 ProSupport and Advanced

Exchange Warranty

its subsidiaries in the U.S. and/or other countries.

MECHANICAL

Cables Included

(1) Power Cable

(1) HDMI cable

(1) DisplayPort cable

(1) VGA cable

Dimensions (W x D x H) and Weight

With stand (lowest position): width: 21.2 in
- depth: 8.2 in - height: 14.9 in - weight: 10 lbs

With stand (highest position): width: 21.2 in
- depth: 8.2 in - height: 20.2 in - weight: 10 lbs
Without stand: width: 21.2 in - depth:

1.9 in - height: 12.8 in - weight: 6.2 lbs

Shipping Weight: 13.14 lbs

Mechanical Display Position

Adjustments

Height, swivel, tilt - Tilt Angle: -5/+21

Swivel Angle: 346 Height Adjustment: 5.3

in VESA Mounting Interface: 100 x 100 mm

Power

Input Voltage: AC 100-240 V (50/60 Hz)

Power Consumption (On mode): 16W

Power Consumption (Typical): 28W

Power Consumption Stand by: 0.3 W

Power Consumption Sleep: 0.3W

Power Consumption (Off Mode): 0.3W

On / Off Switch: Yes