

MON-27-FHD

32 Inch Client Viewing Monitor with Full HD

The 27.01" LED-backlit LCD Monitor delivers Full HD (1080p) visuals with a 16:9 aspect ratio and VA panel for exceptional image quality. Immerse yourself in the vibrant colors and sharp details with a 3000:1 contrast ratio and a 72% NTSC (CIE 1931) and 83% NTSC (CIE 1976) color gamut. Enjoy seamless connectivity with DisplayPort 1.2, VGA, and HDMI, while the adjustable height, swivel, and tilt options provide optimal viewing comfort. This monitor is not only EPEAT Gold and ENERGY STAR certified but also comes with a 5-year 24/7 ProSupport and Advanced Exchange Warranty for your peace of mind.



KEY FEATURES

- ▶ LED-backlit LCD Monitor / TFT Active Matrix
- ▶ 16:9
- ▶ Full HD (1080p) 1920 x 1080 at 60
- ▶ LED Backlight
- ▶ 5Year 24/7 ProSupport and Advanced Exchange Warranty

FOR MORE INFORMATION: bcdvideo.com | sales@bcdinc.com | +1.888.305.4993

TECH SUPPORT: support@bcdinc.com

Copyright © 2026, BCD. All rights reserved. This document is provided for information purposes only. Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

MON-27-FHD

32 Inch Client Viewing Monitor with Full HD

GENERAL

Aspect Ratio

16:9

Backlight Technology

LED Backlight

Brightness

2300 cd/m

Color Gamut

72% NTSC (CIE 1931), 83% NTSC (CIE 1976)

Contrast Ratio

3000:1 / 3000:1 (dynamic)

Diagonal Size

27.01"

Display Type

LED-backlit LCD Monitor / TFT Active Matrix

Native Resolution

Full HD (1080p) 1920 x 1080 at 60

Panel Type

VA

Response Time

Response Time

AUDIO

Speakers

Stereo

3 MON-43-4K 1. he of or T Dell logo is a registered trademark Dell Technologies

CONNECTIVITY

Connectivity Interfaces

(1)DisplayPort 1.2

(1)VGA

(1)HDMI

MON-27-FHD

32 Inch Client Viewing Monitor with Full HD

ENVIRONMENTAL

Environmental Standards

EPEAT Compliant: EPEAT Gold

ENERGY STAR Certified: Yes

Humidity Range Operating

10 - 80% (non-condensing)

Operating Temperature

32 °F - 104°F (0°C - 40°C)

SUPPORT

Warranty

5Year 24/7 ProSupport and Advanced Exchange Warranty
its subsidiaries in the U.S. and/or other countries.

MECHANICAL

Cables Included

- (1)Power Cable
- (1)HDMI cable
- (1)DisplayPort cable
- (1)VGA cable

Dimensions (W x D x H) and Weight

With stand (lowest position): width: 24.1 in
- depth: 8.6 in - height: 16 in - weight: 12.8 lbs

With stand (highest position): width: 24.1 in
- depth: 8.6 in - height: 21.1 in - weight: 12.8 lbs
Without stand: width: 24.1 in - depth: 2 in - height: 14.3 in - weight: 8.6 lbs

Shipping Weight: 17.04 lbs

Mechanical Display Position

Adjustments

Height, swivel, tilt - Tilt Angle: -5/+21
Swivel Angle: 346 Height Adjustment: 5.3 in
in VESA Mounting Interface: 100 x 100 mm

Power

Input Voltage: AC 100-240 V (50/60 Hz)
Power Consumption (On mode): 17 W
Power Consumption (Typical): 30W
Power Consumption Stand by: 0.3 W
Power Consumption Sleep: 0.3W
Power Consumption (Off Mode): 0.3 W
On / Off Switch: Yes