



### Overview



- |                          |  |                     |  |
|--------------------------|--|---------------------|--|
| <b>1. Menu</b>           | Opens, selects or exits the OSD menu.  | <b>4. OK/Auto</b>   | If the OSD menu is on, press to select the highlighted menu item. If the OSD menu is inactive, press to activate the auto adjustment feature to optimize the screen image. |
| <b>2. Minus "-"</b>      | If the OSD menu is on, press to navigate backward through the OSD menu and decrease adjustment levels.   | <b>5. Power</b>     | Turns the monitor on or off.   |
| <b>3. Plus "+"/Input</b> | If the OSD menu is on, press to navigate forward through the OSD menu and increase adjustment levels.<br>If the OSD menu is inactive, press to activate the source button that chooses the video signal source input (VGA or DVI). | <b>6. Power LED</b> | LED:<br>fully powered = blue;<br>sleep mode = amber;<br>sleep timer mode = flashing amber.   |

### Overview



Use two HP V241 23.6-inch monitors combined with an HP Adjustable Dual Display Stand (AW664AA) for a small footprint, high productivity work solution.

(Multi-monitor support depends on your PC capability. Monitors and stands sold separately)

### Model

E5Z68A8

### Technical Specifications

<b>Panel</b>	<b>Type</b>	TN (Twisted Nematic) LED Backlit LCD
	<b>Viewable Image Area</b> (diagonal)	<b>59,8 cm</b> (23.6 in) widescreen, diagonally measured
	<b>Active Area</b> (W x H)	<b>52,12 x 29,32 cm</b> (20.52 x 11.54 in)
	<b>Aspect Ratio</b>	16:9
	<b>Viewing Angle</b> (typical)*	Up to 170° horizontal/160° vertical (10:1 minimum contrast ratio)
	<b>Brightness</b> (typical)*	250nits (cd/m <sup>2</sup> )
	<b>Static Contrast Ratio</b> (typical)*	1000:1
	<b>Dynamic Contrast Ratio</b> (typical)*	3,000,000:1
	<b>Response Rate</b> (typical)*	5 ms (On/Off)
	<b>Pixel Pitch</b>	0.2715 mm
	<b>Backlight Lamp Life</b> (to half brightness)*	40,000 hours minimum
	<b>Color Gamut</b> (typical)*	72%
	<b>Color Support**</b>	Can display up to 16.7 million colors
<p>*All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower. ** With the use of FRC technology.</p>		
<b>On Screen Display (OSD) Controls</b>	<b>Buttons or Switches</b>	Menu, Minus ("-"), Plus ("+")/Source, OK/Auto, Power
	<b>Languages</b>	10 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese and S-Chinese)
	<b>User Controls</b>	Brightness, Contrast, Image Control, OSD control, Languages, Color, Management, Information, Factory Reset, Input Control, Exit
<b>Signal Interface/ Performance</b>	<b>Horizontal Frequency</b>	24 to 94 kHz
	<b>Vertical Frequency</b>	50 to 76 Hz
	<b>Native Resolution</b>	1920 x 1080 @ 60 Hz
	<b>Preset VESA Graphic Modes</b> (non-interlaced)	1920 x 1080 @ 60 Hz
		1680 x 1050 @ 60 Hz
		1600 x 900 @ 60 Hz
		1440 x 900 @ 60 Hz
		1280 x 1024 @ 60 Hz
	1280 x 720 @ 60 Hz	
	1024 x 768 @ 60 Hz	
	800 x 600 @ 60 Hz	
	720 x 400 @ 70 Hz	
	640 x 480 @ 60 Hz	
	<b>Maximum Pixel Clock Speed</b>	170 MHz

### Technical Specifications

	<b>User Programmable Modes</b>	Yes (10)	
	<b>Anti-Glare</b>	Yes	
	<b>Default Color Temperature</b>	6500 K	
<b>Video/Other Inputs</b>	<b>Plug and Play</b>	Yes	
	<b>Input Connectors</b>	VGA (analog), DVI-D (HDCP support on DVI-D)	
	<b>USB</b>	N/A	
	<b>Video Cables</b>	(1)VGA, (1)DVI-D	
	<b>Video Cable Lengths</b>	<b>1,8 m</b> (5.9 ft)	
	<b>Audio</b>	N/A	
<b>Power</b>	<b>Power Supply</b>	Internal	
	<b>Input Power</b>	90 - 265 VAC at 45 - 63 Hz	
	<b>Typical Power Consumption</b>	26 W	
	<b>Maximum</b>	30 W	
	<b>Power Saving</b>	0.5 W	
	<b>Power Cable Length</b>	<b>1,9 m</b> (6.2 ft)	
<b>Mechanical</b>	<b>Dimensions (W x D x H)</b>	<b>Unpacked w/ stand</b>	<b>56,33 x 20,41 x 41,24 cm</b> (22.19 x 8.04 x 16.25 in)
		<b>Unpacked w/o stand (head only)</b>	<b>56,33 x 4,69 x 34,77 cm</b> (22.19 x 1.85 x 13.7 in)
		<b>Packaged</b>	<b>63,4 x 12,5 x 47,5 cm</b> (24.98 x 4.93 x 18.72 in)
		<b>Base area (footprint)</b>	<b>21,91 x 20,41 cm</b> (8.63 x 8.04 in)
	<b>Weight</b>	<b>Head only</b>	<b>3,7 kg</b> (8.2 lb)
		<b>Unpacked</b>	<b>4 kg</b> (8.8 lb)
		<b>Packaged</b>	<b>5,8 kg</b> (12.8 lb)
	<b>Tilt Range</b>	-5° to + 20°	
	<b>Swivel Range</b>	N/A	
	<b>Height Adjustable</b>	N/A	
	<b>Pivot Rotation</b>	N/A	
	<b>Base</b>	Detachable	
<b>Environmental</b>	<b>Temperature – Operating</b>	<b>5° to 35° C</b> (41° to 95° F)	
	<b>Temperature– Non-operating</b>	<b>-20° to 60° C</b> (-4° to 140° F)	
	<b>Humidity – Operating</b>	20% to 80% non-condensing	
	<b>Humidity – Non-operating</b>	5% to 95%, 38.7° C max wet-bulb	
	<b>Altitude – Operating</b>	<b>0 to 5,000 m</b> (16,404 ft)	
	<b>Altitude – Non-operating</b>	<b>0 to 12,192 m</b> (0 to 40,000 ft)	

### Technical Specifications

<b>White LED Backlights</b>	Yes
<b>CCFL Panel</b>	No
<b>Arsenic-Free Display Glass</b>	Yes
<b>Low Halogen<sup>4</sup></b>	No
<b>Mercury-Free Display Backlighting</b>	Yes

### Environmental Data

#### Eco-Label Certifications & declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- US ENERGY STAR<sup>®</sup>
- EPEAT<sup>®</sup> Silver registered in the United States. See <http://www.epeat.net> for registration status in your country

#### Energy Consumption (in accordance with US ENERGY STAR<sup>®</sup> test method)

	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 60Hz</b>
Normal Operation	17.5 W	18.1 W	17.8 W
Sleep	0.3 W	0.38 W	0.29 W
Off	0.21 W	0.28 W	0.2 W

#### Heat Dissipation\*

	<b>115VAC, 60Hz</b>	<b>230VAC, 50Hz</b>	<b>100VAC, 60Hz</b>
Normal Operation	60 BTU/hr	62 BTU/hr	61 BTU/hr
Sleep	1 BTU/hr	1 BTU/hr	1 BTU/hr
Off	1 BTU/hr	1 BTU/hr	1 BTU/hr

\* Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

#### Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2002/95/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive - 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the Silver level, see [www.epeat.net](http://www.epeat.net)
- Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.
- This product contains 0 % post-consumer recycled plastic (by wt.)
- This product is 98.6 % recycle-able when properly disposed of at end of life.

#### Packaging Materials

<b>External:</b>	PAPER/Paper	750 g
<b>Internal:</b>	PLASTIC/EPS (Expanded Polystyrene)	449 g

### Technical Specifications

PLASTIC/EPE-Expanded Polyethylene	26 g
PLASTIC/Other plastics unknown	3 g

#### RoHS Compliance

Hewlett-Packard is committed to compliance with all applicable environmental laws and regulations, including the European Union Restriction of Hazardous Substances (RoHS) Directive. HP's goal is to exceed compliance obligations by meeting the requirements of the RoHS Directive on a worldwide basis. By July 1, 2006, RoHS substances will be virtually eliminated (virtually = to levels below legal limits) for all HP electronic products subject to the RoHS Directive, except where it is widely recognized that there is no technically feasible alternative (as indicated by an exemption under the EU RoHS Directive).

#### Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at: <http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf>):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants - may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel - finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) - except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)

#### Packaging

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in

### Technical Specifications

- packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

#### End-of-life Management and Recycling

Hewlett-Packard offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: <http://www.hp.com/go/reuse-recycle> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: <http://www.hp.com/go/recyclers>. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

#### Hewlett-Packard Corporate Environmental Information

For more information about HP's commitment to the environment:

Global Citizenship Report

<http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html>

Eco-label certifications

<http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html>

ISO 14001 certificates:

<http://www.hp.com/hpinfo/globalcitizenship/environment/operations/envmanagement.html>

#### Options (sold separately)

##### HP LCD Monitor Quick Release - Part number EM870AA<sup>1</sup>

An easy-to-use, VESA-compliant, LCD monitor mounting solution that allows you to quickly and securely attach an LCD monitor to a variety of stands, brackets, arms or wall mounts. For more information, refer to this product's QuickSpecs document.

##### HP USB Graphics Adapter - Part number NL571AA

Enables connection of up to six simultaneous displays to help you boost productivity and multi-task across several open applications. Use one Adapter to bridge between a notebook or desktop PC and second monitor or use multiple Adapters to connect several displays to each other.

##### HP Business PC Security Lock Kit - Part number PV606AA

Attaches to the rear of the PC with a six-foot steel cable that can be used to secure a PC or peripherals such as mice, keyboards, monitors or USB security devices to protect them against unauthorized removal by physically connecting the system to an anchor point.

##### HP Single Monitor Arm - Part number BT861AA

The flexible design of the HP Single Monitor Arm provides a seemingly endless range of display adjustments with an amazing 13 inches of lift, 50 degrees of tilt, and 360 degrees of pan and rotation - all at your fingertips -- helping you stay comfortable and productive throughout the day.

##### HP Adjustable Dual Display Stand - Part Number AW664AA

Premium space-saving dual screen solution provides access to more monitor real estate and makes it possible to manage multiple applications simultaneously. Weight adjustable for dual monitors from 17-24". Rotate displays into portrait/landscape positions.

### Technical Specifications

<b>What's in the box?</b>	<b>Monitor and Accessories</b>	HP V241 23.6-inch LED Backlit Monitor; VGA cable; AC Power cable
	<b>Documentation</b>	Printed documentation and CD
	<b>Featured Software</b>	Yes, HP Display Assistant
<b>Other</b>	<b>User Guide Languages</b>	English, Arabic, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Kazakh, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.
	<b>Warranty Languages</b>	English, Arabic, Czech, Danish, Dutch, Finnish, French, German, Greek, Hungarian, Italian, Kazakh, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and Turkish.
	<b>Color</b>	Black
	<b>VESA External Mounting</b>	Yes (one set of standard 4-hole pattern, 100 mm)
	<b>Security Lock-Ready</b>	Yes
	<b>Country of Origin</b>	China
<b>Certification and Compliance</b>		CB ,FCC, ICES, TUV, TUV-GS, TCO, ETL, S-mark, ENERGY STAR®, EPEAT® Silver <sup>3</sup>
<b>Compatibility</b>		Compatible with platforms using the VESA standard video modes. Recommended for use with HP products.
<b>Service and Warranty</b>		Protected by HP, including a 3 year standard limited warranty. Optional Care Pack Services are extended service contracts which go beyond your standard warranties. <sup>2</sup>

© Copyright 2013 Hewlett-Packard Development Company, L.P.

ENERGY STAR® is a US registered mark of the United States Environmental Protection Agency.

<sup>1</sup>The HP Quick Release has been designed to support a maximum of up to 24 lbs (10.9 kg) for all devices mounted. Because mounting surfaces vary widely and the final mounting method and configuration may vary, mounting fasteners are not supplied (other than the VESA-compliant screws). HP recommends that you consult with a qualified engineering, architectural or construction professional to determine the appropriate type and quantity of mounting fasteners required for your application and to ensure that your mounting solution is properly installed to support applied loads.

<sup>2</sup>HP Care Pack Services are sold separately. Service levels and response times for HP Care Pack Services may vary depending on your geographic location. Service starts from date of hardware purchase. Restrictions and limitations apply. See [www.hp.com/go/cpc](http://www.hp.com/go/cpc) for details.

<sup>3</sup>EPEAT® Silver registered models of this product are available where HP registers commercial display products. See [www.epeat.net](http://www.epeat.net) for registration status in your country.

<sup>4</sup>External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.