

Safeguard Video Servers and Network Devices from Power Outages

The compact floor, desk, or wall mount BCD-XST UPS is a single phase standby UPS designed to deliver power protection to network switches, workstations, and other connected video devices. Vital to any IP video system, it provides full protection against discharge, overcharge, short-circuit, and thermal damage.

KEY FEATURES

- Plug and play functionality
- Cold start from battery
- Floor, desk, or wall mount
- Compact design for quick installation
- Full protection from: discharge, overcharge, short circuit, and thermal damage



USB Interface and Communications



Cold Start Functionality



Auto Restart Ability



Two-Year Warranty



Back

Data Sheet

Standby UPS

INPUT	
Capacity	800VA (480W)
Voltage	120VAC
Frequency	60 Hz
OUTPUT	
Voltage	120VAC
Waveform	Sine wave (normal), simulated sine wave (battery mode)
Frequency	50 / 60 Hz +/- 1 Hz
Transfer Time	2 - 6 ms
MECHANICAL	
Form Factor	Small Form
Battery Type	Sealed, maintenance free lead acid
Battery Quantity and Size	(1) 12V 9AH
Recharge	8 hours to 90% capacity
Input Line Cord	5' (1.5m) input with 5-15P Plug
Output Receptacles	(4) 5-15R
Communications Interface	(1) USB Port with Communications Cable and Shutdown Software
Operating Temperature	(Min) 32°F to (Max) 104° F [(Min) 0°C to (Max) 40° C]
Operating Humidity	0 ~ 90% (non-condensing)
Altitude	11,500 ft (3505.2m) above sea level
Dimensions (WxDxH)	3.2" x 8.9" x 8.1" (81.28mm x 226.06mm x 205.74mm)
Max. Weight	6.8 lbs. (3.08 kg)
Warranty	Two-Year Warranty